

Solargenix Energy Advanced Parabolic Trough Development

R.C. Gee
Solargenix Energy

M.J. Hale
National Renewable Energy Laboratory

*Presented at the 2005 DOE Solar Energy Technologies
Program Review Meeting
November 7–10, 2005
Denver, Colorado*

Conference Paper
NREL/CP-550-39206
November 2005

NREL is operated by Midwest Research Institute • Battelle Contract No. DE-AC36-99-GO10337



NOTICE

The submitted manuscript has been offered by an employee of the Midwest Research Institute (MRI), a contractor of the US Government under Contract No. DE-AC36-99GO10337. Accordingly, the US Government and MRI retain a nonexclusive royalty-free license to publish or reproduce the published form of this contribution, or allow others to do so, for US Government purposes.

This report was prepared as an account of work sponsored by an agency of the United States government. Neither the United States government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or any agency thereof.

Available electronically at <http://www.osti.gov/bridge>

Available for a processing fee to U.S. Department of Energy and its contractors, in paper, from:

U.S. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831-0062
phone: 865.576.8401
fax: 865.576.5728
email: <mailto:reports@adonis.osti.gov>

Available for sale to the public, in paper, from:

U.S. Department of Commerce
National Technical Information Service
5285 Port Royal Road
Springfield, VA 22161
phone: 800.553.6847
fax: 703.605.6900
email: orders@ntis.fedworld.gov
online ordering: <http://www.ntis.gov/ordering.htm>



Solargenix Energy Advanced Parabolic Trough Development

Randy C. Gee¹ and Mary Jane Hale²

¹Solargenix Energy, Arvada, Colorado, RandyCGee@comcast.net

²National Renewable Energy Laboratory, Golden, Colorado, Mary_Jane_Hale@nrel.gov

ABSTRACT

The Solargenix Advanced Trough Development Project was initiated in the Year 2000 with the support of the DOE CSP Program and, more recently, with the added support of the Nevada Southwest Energy Partnership. Parabolic trough plants are the most mature solar power technology, but no large-scale plants have been built in over a decade. Given this lengthy lull in deployment, our first Project objective was development of improved trough technology for near-term deployment, closely patterned after the best of the prior-generation troughs. The second objective is to develop further improvements in next-generation trough technology that will lead to even larger reductions in the cost of the delivered energy. To date, this Project has successfully developed an advanced trough, which is being deployed on a 1-MW plant in Arizona and will soon be deployed in a 64-MW plant in Nevada. This advanced trough offers a 10% increase in performance and over a 20% decrease in cost, relative to prior-generation troughs.

1. Objectives

Solargenix Energy has committed to near-term deployment of an improved parabolic trough that is closely patterned after the best of the prior-generation troughs used at the SEGS plants, as well as further advancing the state of the art of parabolic troughs through R&D that will result in a next-generation trough with even lower installed costs. Accordingly, the Solargenix Energy Advanced Parabolic Trough Development Project has two primary objectives:

Objective 1: Development of an improved parabolic trough module that will be used in near-term SEGS plants.

Objective 2: R&D that will lead to the next-generation parabolic trough, with even further cost reductions.

All project work related to both of these objectives addresses the key technical barriers for trough technology as described in the CSP Subprogram's 2005 Multi-Year Plan: "improving the efficiency and reducing the installed capital cost of the solar field."

2. Technical Approach

The Solargenix Energy Advanced Parabolic Trough Development Project builds upon the basic knowledge and excellent operational history¹ of the SEGS plants that were constructed during the years 1984 to 1992. But since no large-scale SEGS projects have been built in over a decade, our general technical approach has been to build upon the most successful elements of these plants, but reduce collector costs and improve performance. The project's technical approach is also aligned with the CSP Subprogram's focus areas as outlined in the Multi-Year

Plan: performance improvement, cost reduction, deployment support.

With a goal of near-term deployment (see Objective 1 above), we have first focused on the trough's prime targets for cost reduction (e.g. the trough structure) or where component development priorities (e.g. sun tracking controls). But we retained the same 8-m trough module length, and use the same glass mirrors successfully deployed at the SEGS plants. This approach reduces the time required to develop an advanced trough, and also reduces risks associated with the planned first-in-a-decade trough projects, a key consideration with the financial community that invests in these trough plants.

In addition to the R&D activities aimed at preparation for near-term trough deployment, we have also undertaken R&D that is somewhat longer term and/or that requires a somewhat larger technical departure from the parabolic troughs that have been operating at the SEGS plants. Here our goal is to develop a next-generation trough with even greater cost reductions (see Objective 2 above).

3. Results and Accomplishments

Prior Project work resulted in the definition of an advanced parabolic trough that uses a lightweight space frame structure, is twice the length of the prior-generation LS-2 collector and incorporates newly developed and improved subsystems (i.e. sun tracking controls, support pylons and drive units). Analysis and evaluation showed that the new Solargenix trough offers a 10% increase in performance and an 18% decrease in installed cost relative to the prior-generation². Additional work during FY'05 has focused on further advancing this design through prototype deployment and testing, followed by optimization that incorporates "lessons learned" from prototype testing.

3.1 Field Deployment of Advanced Trough Structure

The design of an advanced 8-meter long parabolic trough structural framework, which supports the glass mirrors that concentrate sunlight onto the receiver tubes, was completed and successfully deployed for field-testing at the Eldorado Valley Test Site near Boulder City.



Fig.1 . Deployment of advanced trough structure.

The trough structure was designed to be field assembled (to reduce transportation costs from the factory to the project site), and to have reduced manufactured cost. This large emphasis on the structure of a parabolic trough is warranted because the structure has historically represented about 40% of the total collector cost, the highest single subsystem cost³. The new space frame was fitted with curved glass mirrors and readied for field-testing, as shown in Figure 1.

3.2 Space Frame Optimization

Since the Solargenix SCA uses a field-assembled space frame, the labor required for assembly of these frames is an important cost factor. Twenty-four space frames were assembled to determine how the process could be made more efficient. Three design improvements were identified⁴ that have reduced assembly time nearly in half.

Further cost reductions were then identified by optimizing the frame structures for each module along the 100-m length of the collector (modules other than those adjacent to the drive, where lower torsional strength is required). Analysis shows this reduces the manufactured cost of the collector by another 8%. Two lighter weight space frames have been erected at the Eldorado Valley Test Site for field-testing.

3.3 Optical Testing at NREL

A Solargenix space frame has been assembled at NREL. The space frame is being used in NREL's Optical Laboratory to examine, characterize, and further evaluate the concentrator optics, with the objective of further improving the optical quality of the concentrator.



Fig. 2. Optical testing at NREL's optical lab

3.4 Sun Tracking and Solar Field Controls Development

Completely new sun tracking and solar field controls were a high-priority development need because the prior-generation SEGS controls are obsolete. To date, a new Advanced Local Controller (AdLoC) has been developed and readied for field deployment. The AdLoC controls the sun-tracking movements of the collector. Each AdLoC is connected through a network, to the Field Control Server (FCS), which has also been recently developed as part of this Project. The FCS monitors the AdLoCs in the field, collects real-time data and alarm conditions, and controls the overall operation of the AdLoC field. All bench testing has been completed and AdLoC and FCS controllers are ready for field-testing.

3.5 Full-Scale Wind Load Tests

Wind load experiments are underway using full-scale trough collectors to provide a comparison with loads predicted from wind tunnel tests. The results of these experiments will better quantify wind loads, which govern the structural design of a parabolic trough. All monitoring equipment is in

place and data taking has commenced. Data taking will continue until enough data is obtained to allow comparison with the loads predicted from prior wind tunnel tests.

3.6 Development of a Next-Generation Space Frame

A new space frame structure has been developed that significantly reduces the number of parts needed for each trough module. Weight and cost reductions are currently being analyzed, but the design has been completed and a prototype space frame has just been erected at the Eldorado Valley Test Site for evaluation and field-testing.

4. Conclusions

The Solargenix Advanced Trough Development Project has successfully developed a new generation of parabolic troughs, with improved performance and significantly reduced cost compared to the best of the prior-generation troughs. This satisfies the need for an advanced trough ready for near-term deployment, and it is in fact currently being deployed in trough plants.

Next steps of this Project include: the construction of a thermal loop at the Eldorado Valley Test Site for extended field testing capabilities, and continuation of advanced component R&D leading to the next generation of parabolic troughs with even further increases in performance and further reductions in installed collector costs.

ACKNOWLEDGEMENTS

Solargenix Energy would like to acknowledge the support of DOE/NREL and the NSWEP members, in particular UNLV.

REFERENCES

- ¹Cohen, G.E.; Kearney, D.W.; Kolb, G.J. (1999). Final Report on the Operation and Maintenance Improvement Program for CSP Plants.
- ²Task Report to NREL: *Solargenix Collector Design with Cost and Performance Comparisons*, Dec. 21, 2004.
- ³H. Price and D. Kearney, [Parabolic Trough Technology Roadmap: A Pathway for Sustained Development and Deployment of Trough Technology](#), NREL, January 1999.
- ⁴Task Report to NREL: *Solargenix Energy Space Frame Assembly-Efficiency Report*, March 9, 2005.

MAJOR FY 2005 PUBLICATIONS

- NSWEP Progress Report, *Solargenix Advanced Parabolic Trough Pilot Project*, Randy Gee; NSWEP Program Review Meeting; July 22, 2005.
- Sandia National Laboratories Performance Report, *Final Test Results for the Solargenix Prototype Collector Module*, Tim Reynolds and Rod Mahoney; May 17, 2005.
- Interim Progress Report to SunLab, *Solargenix Energy Advanced Parabolic Trough Development Progress Report*, Randy Gee; August 18, 2005.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ORGANIZATION.

1. REPORT DATE (DD-MM-YYYY) November 2005		2. REPORT TYPE Conference Paper		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE Solargenix Energy Advanced Parabolic Trough Development				5a. CONTRACT NUMBER DE-AC36-99-GO10337	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) R.C. Gee and M.J. Hale				5d. PROJECT NUMBER NREL/CP-550-39206	
				5e. TASK NUMBER CP06.5001	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Renewable Energy Laboratory 1617 Cole Blvd. Golden, CO 80401-3393				8. PERFORMING ORGANIZATION REPORT NUMBER NREL/CP-550-39206	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S) NREL	
				11. SPONSORING/MONITORING AGENCY REPORT NUMBER	
12. DISTRIBUTION AVAILABILITY STATEMENT National Technical Information Service U.S. Department of Commerce 5285 Port Royal Road Springfield, VA 22161					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT (Maximum 200 Words) The Solargenix Advanced Trough Development Project was initiated in the Year 2000 with the support of the DOE CSP Program and, more recently, with the added support of the Nevada Southwest Energy Partnership. Parabolic trough plants are the most mature solar power technology, but no large-scale plants have been built in over a decade. Given this lengthy lull in deployment, our first Project objective was development of improved trough technology for near-term deployment, closely patterned after the best of the prior-generation troughs. The second objective is to develop further improvements in next-generation trough technology that will lead to even larger reductions in the cost of the delivered energy. To date, this Project has successfully developed an advanced trough, which is being deployed on a 1-MW plant in Arizona and will soon be deployed in a 64-MW plant in Nevada. This advanced trough offers a 10% increase in performance and over an 20% decrease in cost, relative to prior-generation troughs.					
15. SUBJECT TERMS Photovoltaics; solar; parabolic trough; PV; NREL					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UL	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NUMBER (Include area code)