

Application of a Sweating Manikin Controlled by a Human Physiological Model and Lessons Learned

J. Rugh and J. Lustbader

*Presented at the 6th International Thermal Manikin and Modeling Meeting
Hong Kong, China
October 16–18, 2006*

Conference Paper
NREL/CP-540-40435
November 2006

NREL is operated by Midwest Research Institute • Battelle Contract No. DE-AC36-99-GO10337



NOTICE

The submitted manuscript has been offered by an employee of the Midwest Research Institute (MRI), a contractor of the US Government under Contract No. DE-AC36-99GO10337. Accordingly, the US Government and MRI retain a nonexclusive royalty-free license to publish or reproduce the published form of this contribution, or allow others to do so, for US Government purposes.

This report was prepared as an account of work sponsored by an agency of the United States government. Neither the United States government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or any agency thereof.

Available electronically at <http://www.osti.gov/bridge>

Available for a processing fee to U.S. Department of Energy and its contractors, in paper, from:

U.S. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831-0062
phone: 865.576.8401
fax: 865.576.5728
email: <mailto:reports@adonis.osti.gov>

Available for sale to the public, in paper, from:

U.S. Department of Commerce
National Technical Information Service
5285 Port Royal Road
Springfield, VA 22161
phone: 800.553.6847
fax: 703.605.6900
email: orders@ntis.fedworld.gov
online ordering: <http://www.ntis.gov/ordering.htm>



Application of a Sweating Manikin Controlled by a Human Physiological Model and Lessons Learned

John P. Rugh, Jason Lustbader

National Renewable Energy Laboratory, Golden, Colorado, U.S.A.

Abstract

The National Renewable Energy Laboratory (NREL) has developed a suite of thermal comfort tools to help develop smaller and more efficient climate control systems in automobiles. The tools consist of a thermal comfort manikin, physiological model, and psychological model that are linked together to assess comfort in a transient non-homogeneous environment. The manikin and models have been validated against physiological data that are available in the literature and test subject data that were used to develop the psychological model. The manikin was used in NREL's Vehicle Climate Control Laboratory (VCCL) to assess the impact of an automotive ventilated seat on thermal comfort and fuel economy. In a test program with NASA, the manikin was used to evaluate liquid cooling garments (LCGs) worn underneath spacesuits.

1. Introduction

Our goal at NREL is to help the automotive industry reduce the fuel used for air conditioning (A/C). NREL is investigating techniques to reduce the peak soak temperature, which allows the A/C system size to be reduced. We are also looking at improved delivery systems and alternative methods to cool the passenger compartment, which will reduce the power requirements of a climate control system.

Since a key requirement is to maintain or enhance passenger comfort, we need to understand how advanced cooling techniques will affect human thermal comfort. NREL has developed a portfolio of thermal comfort tools, including an ADvanced Automotive Manikin (ADAM), Human Thermal Physiological Model, and Human Thermal Comfort Empirical Model to assess comfort in automobile passenger compartments¹.

2. Thermal Comfort Tools

The integrated human thermal comfort system consists of the thermal manikin controlled by a finite element physiological model of the human body. The thermal manikin is a surface sensor that measures the rate of heat loss at 120 independently controlled zones. The skin heat transfer rates are sent to the physiological model, which computes the skin and internal temperature distribution and surface sweat rates. This information is then sent back to the manikin, which generates the prescribed skin temperatures, surface sweat rates and breathing rates. As the model steps forward in time, this loop provides a transient measurement tool. The psychological comfort model uses temperature data from the physiological model to predict the local and global thermal comfort as a function of local skin and core temperatures and their rates of change. Using this manikin as a sensor simplifies the complex clothing and environmental heat transfer into local heat loss measurements from the skin.

2.1 *ADvanced Automotive Manikin*

The manikin is approximately 175 cm tall and was sized to comply with the 50th percentile western person. He weighs approximately 61 kg; heavy enough to compress an automotive seat and give a realistic contact area. The manikin's skeleton is composed of laminated carbon fibre, which supports its structure, houses all internal components and provides mounting locations for surface zones².

The manikin's fundamental components are the 126 individual surface segments, each with a typical surface area of 120 cm². Each segment (Figure 1) is a stand-alone device with integrated heating, temperature sensing, sweat distribution and dispensing, a heat flux gauge, and a local controller to manage the closed-loop operation of the zone. The high-thermal conductivity of the all-metal sweating surface yields increased thermal uniformity and response speed. A high-porosity layer within the surface provides lateral sweat distribution while the lower porosity exterior promotes uniform sweat across the surface. Distributed resistance wire provides uniform heating across the zone surface. Six segments are controlled in pairs, and result in 120 separately controlled zones. A single zone controller, including flow control, is mounted directly on the back of each segment. The skin temperature of each zone is determined by an array of thermistors (typically four) on each zone. A heat flux gauge, integrated onto the internal surface of each zone, measures heat transfer between the surface zones and the internal body cavity.




Figure 1 Manikin Segment

ADAM was built by Measurement Technology Northwest in Seattle, Washington. The characteristics that make ADAM a unique thermal manikin are:

- High spatial resolution (120 zones)
- Self-contained
- Uniform sweating and heating over the entire area of the manikin
- Finite element physiological model control.

2.2 *Human Thermal Physiological Model*

The NREL Human Thermal Physiological Model is a three-dimensional transient finite element model of the human body. The model simulates the human internal thermal physiological systems, such as muscle and blood, and thermoregulatory responses. The model was developed with the commercially available finite element software ANSYS. This software computes heat flow by conduction, convection and mass transport of the blood. The arms and legs consist of bone, muscle, fat and skin. There are additional lung and abdominal tissues in the torso and brain tissues in the head.

Blood flow is modelled with a network of supply and return pipe elements within each body zone. The diameter of the pipes decreases from the centre of each zone outward, toward the skin and extremities. The thermoregulatory system controls physiological responses, such as vasoconstriction/dilation, sweating, shivering, and metabolic changes.

2.3 *Human Thermal Comfort Empirical Model*

The University of California, Berkeley performed 109 human subject tests in its Controlled Environmental Chamber under a range of steady-state and transient thermal conditions to explore the relationship between local thermal conditions and perception of local and overall thermal comfort. Core and local skin temperature data and subjective data were used to develop a predictive model of thermal sensation and perception^{3,4}.

Zhang concluded that overall comfort is not an additive function of all local perceptions, but instead is “complaint” driven. This means that the most uncomfortable body parts drive the overall thermal comfort perception. We encountered difficulties using this approach. Using the data available, we found a straight average to be a better predictor of subjective responses. This topic may warrant further investigation.

3. Validation Tests

3.1 Steady-State Conditions

NREL ran a series of tests to compare ADAM's skin temperatures with steady-state subject data from Werner and Reents⁵. We placed ADAM nude and horizontal in our Manikin Environmental Chamber. The chamber was maintained at a uniform temperature with negligible airflow. We ran ADAM with physiological model control. Although the actual metabolic rates of the subjects are unknown, the suggested 45 W/m^2 for a reclining human from the American Society of Heating, Refrigerating and Air-Conditioning Engineers (ASHRAE) Fundamentals Handbook⁶ was applied to the human in the model.

We compared the resulting core and skin temperatures with the Werner and Reents data in Fig. 2 for an air temperature of 23.2°C . The manikin/model tended to predict warmer skin temperatures than those measured, with a maximum deviation of 4.2°C . The overall trends were encouraging: the core temperature agreed within 0.6°C , and skin temperatures decreased in regions further from the torso.

Figure 3 shows the comparison for an air temperature of 30°C . The core temperature was within 0.1°C , and the maximum skin temperature deviation was 2.1°C at the hands. The manikin and model under-predict skin temperatures at higher ambient air temperatures. The core temperature matched exactly, but the maximum under-prediction was 2.5°C at the hands.




Figure 2 ADAM/Human Comparison, $T_{\text{air}}=23.2^\circ\text{C}$




Figure 3 ADAM/Human Comparison, $T_{\text{air}}=30^\circ\text{C}$

Initial results indicate the manikin with physiological model control yields human-like skin temperature distribution. Compared to data from Werner, the skin temperatures were within approximately $+4.2/-2.5^\circ\text{C}$ for a wide range of ambient air temperatures. The core temperatures agreed to within 0.6°C . Details on the testing and analysis are available in Rugh and Bharathan⁷.

3.2 Transient Conditions

During our automotive testing, we noted the predicted core temperature responded quickly when ADAM was moved into a hot passenger compartment environment. Xu and Werner⁸ and Haslan and Parsons⁹ show a 0.004-0.007 °C/min change in core temperature during temperature step-up experiments. Similar transient step change tests were performed at NREL. ADAM and the subject each were dressed in cotton pants, short sleeve shirt, undergarment and socks. The subject core temperature was monitored with a wireless pill that was injected ~4 hours prior to the test. The Manikin Environmental Chamber was conditioned to 38°C and 50% relative humidity. ADAM and the subject were seated and conditioned in a 21°C office environment for ~3 hr. Then both were moved to the Manikin Environmental Chamber for 2 hr. Figure 4 shows the core temperature of the two NREL subjects was similar to the Xu and Werner data, while ADAM's core temperature overshoot. We are looking into the reasons, including the model circulation system and the lag between commanded sweat and actual evaporation.




Figure 4 T_{core} during Step-up Temperature Test

The Manikin Environmental Chamber was conditioned to 38°C and 50% relative humidity. ADAM and the subject were seated and conditioned in a 21°C office environment for ~3 hr. Then both were moved to the Manikin Environmental Chamber for 2 hr. Figure 4 shows the core temperature of the two NREL subjects was similar to the Xu and Werner data, while ADAM's core temperature overshoot. We are looking into the reasons, including the model circulation system and the lag between commanded sweat and actual evaporation.

4. Ventilated Seat Application

Improving the delivery methods for conditioned air in an automobile is an effective way to increase thermal comfort with little energy cost. This reduces A/C needs and thus fuel use. Automotive seats are well suited for effective delivery of conditioned air due to their large contact area with, and close proximity to, the occupants. Normally a seat acts as a thermal insulator, increasing skin temperatures and reducing evaporative cooling of sweat. Ventilating a seat has low energy costs and eliminates this insulating effect while increasing evaporative cooling. W.E.T. Automotive Systems manufactures a ventilated seat that pulls air through the seat cushion and back. We assessed one of these seats using ADAM.

The VCCL at NREL was developed to simulate the soak and cool-down of a vehicle passenger compartment¹⁰. The passenger compartment from a compact car, A to C pillar, was heat soaked using a 963 W/m² ± 23% full spectrum solar simulator for 3.5 hours. During this time, the average room environment was controlled at 31.6°C ± 0.4°C and 30% ± 5% RH. ADAM and the subjects were conditioned in an office environment. The subject entered the heat soaked room, stood for 30 seconds, and then did step exercises for one minute to simulate walking to the car. The subject entered the heat soaked car and took a pre-cool-down thermal comfort and sensation vote. The A/C system was started 45 seconds after the subject entered the vehicle, at which time the first cool-down vote was taken. Thermal comfort and sensation votes followed every two minutes for the duration of the test.

Figure 5 shows that an operating ventilated seat increased the heat loss from ADAM's back and bottom by ~60 W/m² (25-35 minutes into the cool-down) compared to no ventilation (baseline). The seat contact temperature was reduced by ~4.7°C resulting in an overall thermal sensation improvement of 0.28 (on a +4 to -4 scale) shown in Fig. 6. We determined that if the A/C system capacity was reduced by 7% and the ventilated seat was used, the same thermal sensation and comfort as the baseline seat would result. Using NREL's A/C fuel use model¹¹, an estimated 522 million gal/year or 7.5% reduction in U.S. A/C fuel use could be achieved.




Figure 5 Heat Loss from ADAM’s Back and Bottom




Figure 6 ADAM Thermal Sensation

5. Liquid Cooling Garment Application

NASA currently uses LCGs under spacesuits to remove heat from the human body during a spacewalk. Thermally conditioned liquid is circulated through small tubes distributed around the suit. We used ADAM to assess a Shuttle LCG (Fig. 7) as well as an Orlan LCG, a Russian-designed cooling garment¹². NASA uses a comfort curve to determine the inlet flow temperature as a function of metabolic rate for the Shuttle LCG. We tested three points on the curve and two points off the curve. The test is determined to reach steady state when the core temperature stabilizes.

The room temperature was set at 27°C, which yielded a spatially averaged air temperature of 26.6°C around ADAM. The room humidity was maintained at 25%.



Figure 7 Shuttle LCG

A flow rate of 1.81 l/min was used in all tests. It took 3-4 hours to reach steady state for M=275 W and 7 hours for M=350 W. At the higher metabolic rates and inlet temperatures, the core temperature initially overshoots due to a lag in sweat evaporative cooling, which subsequently causes excessive sweating. This sweat (deionised water) flows into the segments, evaporates, and causes a resulting undershoot in core temperature.

Figure 8 shows the core temperature for the Orlan LCG was an average of 0.06°C lower than the Shuttle LCG for all tests. Since the sweat rate is a function of core temperature in the model, the Orlan LCG also has lower sweat rates. The heat transfer to the LCG fluid in Fig. 9 was on average 15 W greater with the Orlan suit indicating the improved heat transfer compared to the Shuttle LCG.




Figure 8 Core Temperatures




Figure 9: Heat Transfer to LCG Fluid

The skin temperature results are not as consistent. While the Orlan LCG resulted in a lower average skin temperature in two cases, a higher average skin temperature resulted during the lowest fluid inlet temperature cases. This is because the Orlan LCG does not have cooling tubes in the calf region. The Shuttle LCG has tubes and subsequently lower calf temperatures. This also lowers the foot temperatures due to cooler blood flow and results in a lower overall average skin temperature. The dashed lower curves in Figure 10 present the average skin temperature for three inlet temperature cases at M=275 W. At Tinlet=17.5°C, the Orlan LCG has a higher average skin temperature. Taking the calves and feet out of the average (solid lines), the Orlan LCG has significantly lower skin temperatures for the M=275 W cases, as well as for the M=350 W and M=200 W cases.




Figure 10 Skin Temperatures

6. Conclusions

Results of validation testing of NREL's thermal comfort tools indicate the manikin with physiological model control yields human-like skin temperature distribution. Comparison with subject data shows the predicted skin temperature distribution of the manikin and model is similar to that of the human subject except for the hand and foot. The manikin and subject data were used in NREL's VCCL to assess the impact of an automotive ventilated seat on thermal comfort and fuel economy. Results show an improvement in thermal comfort with the ventilated seat. This yields a potential 7% reduction in A/C compressor power and 7.5 % reduction in vehicle fuel use. ADAM was successfully used to assess the thermal performance of Shuttle and Orlan LCGs. Comparing results with the same manikin and room conditions, the Orlan LCG had slightly better heat transfer, which resulted in lower core and skin temperatures.

During these previously discussed test programmes, a number of challenges with the manikin and physiological model were encountered. At high metabolic rates or high temperature/humidity environments, it took a long time for the system to reach steady state due to an oscillation in the predicted core temperature. This may be caused by a lag in evaporative cooling compared to the commanded sweat rate or an artifact of the model responding too quickly to changes in skin heat loss. A few segments failed due to broken heaters and controllers, but the large number of segments allowed testing to continue using data from adjacent segments. We reviewed the psychological results (sensation and comfort) and determined an average of local comforts was a better method to calculate the overall comfort than the original correlation.

7. Acknowledgements

The authors gratefully acknowledge the support of the U.S. Department of Energy (DOE) in developing, fabricating, and testing the thermal manikin and physiological model. DOE's Office of FreedomCAR and Vehicle Technologies (OFCVT) supported this work. The authors appreciate the support of Lee Slezak, DOE Program Manager; Terry Penney, NREL's OFCVT Technology Manager; and Barbara Goodman, Director of the NREL Center for Transportation Technologies and Systems. The authors also thank Rob Farrington, Charlie King, and Desikan Bharathan at NREL; Heather Paul and Luis Trevino at NASA; and Goran Bajic at W.E.T. Automotive Systems.

8. References

1. Rugh, J.; Farrington R.; Bharathan, D.; Vlahinos, A.; Burke, R.; Huizenga, C.; and Zhang, H. (2004) Predicting Human Thermal Comfort in a Transient Non-Uniform Thermal Environment, *European Journal of Applied Physiology*, Vol. 92, Number 6, pp. 721-727.
2. Burke, R.; Rugh, J.; and Farrington R. (2003) ADAM – the Advanced Automotive Manikin, 5th International Meeting on Thermal Manikins and Modeling, Strasbourg, France.
3. Zhang, H.; Huizenga, C.; Arens E.; and Wang, D. (2004) Thermal Sensation and Comfort in Transient Non-Uniform Thermal Environments, *European Journal of Applied Physiology*, Vol. 92, Number 6, pp. 728-733, September 2004.
4. Zhang, H. (2004) Human Thermal Sensation and Comfort in Transient and Non-Uniform Thermal Environments, Ph.D. Thesis, U.C. Berkeley.
5. Werner, J. and Reents, T. (1980) A Contribution to the Topography of Temperature Regulation in Man, *European Journal of Applied Physiology*, 1980, 45:87-94.
6. 2001 ASHRAE Fundamentals Handbook, p. 8.7.
7. Rugh, J.; and Bharathan, D. (2005) "Predicting Human Thermal Comfort in Automobiles," Proceedings of the 7th Vehicle Thermal Management Systems Conference, Paper # 2005-01-2008, May 10-12, 2005, Toronto, Canada, Society of Automotive Engineers.
8. Xu, X; and Werner, J. (1997) A Dynamic Model of the Human/Clothing/Environment System, *Applied Human Science-Journal of Physiological Anthropology*, Vol. 16, Num. 2, pp. 61-75.

9. Haslam, R.; and Parsons, K. (1994) Using Computer-Based Models for Predicting Human Thermal Responses to Hot and Cold Environments, *Ergonomics*, Vol 37, Num 3, pp. 399-416.
10. Lustbader, J. (2005) "Evaluation of Advanced Automotive Seats to Improve Thermal Comfort and Fuel Economy," Proceedings of the 7th Vehicle Thermal Management Systems Conference, Paper # 2005-01-2056, May 10-12, 2005, Toronto, Canada, Society of Automotive Engineers.
11. Rugh, J.; Hovland, V.; and Andersen, S. (2004) Significant Fuel Savings and Emission Reductions by Improving Vehicle Air Conditioning, Mobile Air Conditioning Summit, Washington, D.C., April 14-15, 2004.
12. Rugh, J.; King, C.; Paul, H.; Bue, G.; and Trevino, L. (2006) "Phase II Testing of Liquid Cooling Garments Using a Sweating Manikin, Controlled by a Human Physiological Model," Proceedings of the 36th International Conference on Environmental Systems, Paper # 2006-01-2239, July 17-20, 2006, Norfolk, VA, Society of Automotive Engineers.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ORGANIZATION.

1. REPORT DATE (DD-MM-YYYY) November 2006		2. REPORT TYPE Conference Paper		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE Application of a Sweating Manikin Controlled by a Human Physiological Model and Lessons Learned				5a. CONTRACT NUMBER DE-AC36-99-GO10337	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) J. Rugh and J. Lustbader				5d. PROJECT NUMBER NREL/CP-540-40435	
				5e. TASK NUMBER FC06.5000	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Renewable Energy Laboratory 1617 Cole Blvd. Golden, CO 80401-3393				8. PERFORMING ORGANIZATION REPORT NUMBER NREL/CP-540-40435	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S) NREL	
				11. SPONSORING/MONITORING AGENCY REPORT NUMBER	
12. DISTRIBUTION AVAILABILITY STATEMENT National Technical Information Service U.S. Department of Commerce 5285 Port Royal Road Springfield, VA 22161					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT (Maximum 200 Words) Discusses two applications of NREL's suite of thermal comfort tools: one to assess impact of an automotive ventilated seat on comfort and fuel economy, and another to evaluate liquid cooling garments for NASA spacesuits.					
15. SUBJECT TERMS thermal comfort tools; ADAM; thermal manikin; NASA liquid cooling garments; NASA spacesuits; automotive ventilated seating					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UL	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NUMBER (Include area code)