

## Overview of ARIES Research Projects Involving Inverter-Based Resources

Vahan Gevorgian, NREL

Power Electronic Grid Interface (PEGI) Platform Workshop

October 13th, 2020

### **NREL Flatirons Campus**

- Total of 12+ MW variable renewable generation currently
- 7 MVA Controllable Grid Interface (CGI)
- Multi-MW energy storage test facility
- 2.5MW and 5 MW dynamometers (industrial motor drives)
- 13.2 kV medium voltage grid
- 1.5 MW total PV capacity



Research Turbines 2 x 600 kW GE 1.5 MW

### NWTC Controllable Grid Platform



### Main Engineering Challenges for Grids with High Shares of IBRs

- Lowering of system inertia, degrading frequency stability with increasing penetration
- Degrading grid strength, stability in weaker grids
- New protection methods at any level in the grid (low short-circuit current)
- Who and how will be providing grid forming? Why can't we operate all inverters as grid forming? Do we still need grid following? New black-start paradigm? Inrush current issue?
- New stability challenges in inverter dominated grids control interactions and resonances. New stability evaluation methods (impedance-based stability analysis, etc.).
- How to control new transmission technologies FACTS, HVDC, multi-terminal HVDC? New roles for synchronous condensers?
- Frequency stability in future inverter–dominated grids and in 100% grids:
  - Future 1: everything is inverter coupled (even hydro), no synchronizing torque, classic frequency stability becomes irrelevant
  - Future 2: We still have some synch generation at 100% (hydro, CSP, etc.), so classic frequency stability still matters.
- Reliability and resiliency of decentralized and autonomous grids, MVDC/LVDC grids
- High fidelity sensing and new data driven state estimation, control and protection methods
- Cyber security in inverter dominated grids

### 7 MVA Controllable Grid Interface #1

#### **Power rating**

- 7 MVA continuous
- 39 MVA short circuit capacity (for 2 sec)
- 4-wire, 13.2 kV

#### **Possible test articles**

- Types 1, 2, 3 and 4 wind turbines
- PV inverters, energy storage systems
- Conventional generators
- Combinations of technologies

#### Voltage control (no load THD <1%)

- Balanced and un-balanced voltage fault conditions (ZVRT and 140% HVRT) independent voltage control for each phase on 13.2 kV terminals
- Response time 1 millisecond (from full voltage to zero, or from zero back to full voltage)
- Long-term symmetrical voltage variations (+/- 10%) and voltage magnitude modulations (0-10 Hz) – SSR conditions
- Programmable impedance (strong and weak grids)
- Programmable distortions (lower harmonics 3, 5, 7)
- Impedance characterization of inverter-coupled generation
- Full STATCOM functionality

#### **Frequency control**

- Fast output frequency control (3 Hz/sec) within 45-65 Hz range
- 50/60 Hz operation
- · Can simulate frequency conditions for any type of power system
- PHIL capable (coupled with RTDS, Opal-RT, etc.)
- Test-bed for PMU-based wide-area stability controls



#### Capabilities

- Balanced and unbalanced over and under voltage fault ride-through tests
- · Frequency response tests
- Continuous operation under unbalanced voltage conditions
- Grid condition simulation (strong and weak)
- Reactive power, power factor, voltage control testing
- Protection system testing (over and under voltage and frequency limits)
- Islanding operation
- Sub-synchronous resonance conditions
- 50 Hz tests

### 20 MVA Controllable Grid Interface

#### **Power rating**

- Continuous AC rating 19.9 MVA at 13.2kV and 34.5 KV
- Overcurrent capability (x5.7 for 3 sec, x7.3 for 0.5 sec)
- 4-wire 13.2 kV or 35.4 kV taps
- Continuous operational AC voltage range: 0 40 kVAC
- Continuous DC rating 10 MW at 5 kVDC

#### **Possible test articles**

- Types 1, 2, 3 and 4 wind turbines
- PV inverters, energy storage systems
- Conventional generators
- Combinations of technologies / hybrid systems
- Responsive loads

#### Voltage control (no load THD <1%)

- Balanced and unbalanced voltage fault conditions (ZVRT, LVRT and 140% HVRT) independent voltage control for each phase on 13.2 kV and 34.5 kV terminals
- Response time less than 1 millisecond (from full voltage to zero, or from zero back to full voltage)
- Programmable injection of positive, negative and zero sequence components
- Long-term symmetrical voltage variations (+/- 10%) and voltage magnitude modulations (0-10 Hz) – SSR conditions
- Programmable impedance (strong and weak grids, wide SCR range corresponding to a POI with up to 250 MVA of short circuit apparent power)
- Injection of controlled voltage distortions
- Wide-spectrum (0-2kHz) impedance characterization of inverter-coupled generation and loads
- All-quadrant reactive power capability characterization of any system

#### **Frequency control**

- Fast output frequency control (3 Hz/sec) within 45-65 Hz range
- 50/60 Hz operation
- Can simulate frequency conditions for any type of power system
- PHIL capable (can be coupled with RTDS, Opal-RT, Typhoon, etc.)
- Coupled with PMU-based wide-area stability controls validation platform



#### **New features**

- 5 kV MVDC grid simulator (PHIL capable)
- Voltage or current source operation
- Seamless transition between voltage and current source modes
- Emulation of full set of resiliency services:
  - Black start
  - Power system restoration schemes
  - Microgrids
- Flexible configurations are possible when combined with CGI#1:
  - Two independent experiments
  - Parallel operation
  - Back-to-back operation
  - Emulation of isolated, partially or fully grid-connected microgrids

### **SETO Project: PV-BESS Integration**

#### **NREL-First Solar Collaboration**





### SETO Project: Grid Forming PV Inverters

#### **NREL-GE** Collaboration

#### CGI Bus Building Bus CGI bus ES4 250 kW DC Supplies (8x) ES5 Variable speed exhaust fan (2) 2.2 MVA 500V/13.2kV Transformer 3 MW load bank 1.1MW GE Inverter (2x) <u>س</u>لیہ 3x1MVA <del>م</del>لک ۳۳ 3MVA â 2.2 MVA 500V 480V ണന്ന 3 MVA RLC Load Bank 3 MVA 480V/13.2kV Transformer DC PV Simulators **GE PV Inverters** (8x250kW) (2x1000kW) Air Intake Louvers (6) 53' Insulated Shipping Container **GE LV5 inverters** 2MW PV Array Emulator Grid Pad 5

#### GE Grid Forming PV - Project Pad 5 Concept

controls by utility-scale PV inverters

**Objective: Develop and demonstrate grid forming** 

### NREL-PG&E Project: GFM BESS Circuits to Enhance **Reliance of Distribution Grids**





1.5

1.2 1.3 1.4 1.5

1.1 t[s]

### DOE OE Project: SuperFACTS



- Scalable solution for transmission, subtransmission and islanded applications
- All types of grid services (market based, reliability and resiliency)

SuperFacts

Module

- Robust controls
- Grid strength enhancement

Dispatchability

and reliability

services, black start

**BESS MW** 

SuperFacts

Module

SuperFacts

SuperFacts

Module

Condensor

Grid strength, short circuit current, large overcurrent capability, inertia

- Black start resource
- Fully scalable solution



### WETO Project: Wind as Virtual Synch Generator

![](_page_10_Figure_1.jpeg)

Main Objective: Development, implementation and validation of GFM controls using GE generator/converter platform with NREL's 5 MW dynamometer and Controllable Grid Interfaces

- · Provision of reliability services by GFM wind power
- Transient performance by GFM wind power
- Black start and resilience services by GFM wind power

### DOE GMLC: FlexPower Hybrid Plant Demonstration Platform

![](_page_11_Figure_1.jpeg)

### **Optimized Hybrid Energy Systems**

- Validation of design optimization tools and operational strategies for hybrid energy storage systems for provision of grid services at various time scales (ms-s-min-hr-day)
- Development and validation of optimized control theory for hybrid energy storage to provide essential reliability and resiliency services to the grid:
  - Optimal ratios between device level, plant level and system level controls
- Design and operation of hybrid renewable-storage plants for improved dispatchability, increased capacity factors and enhanced grid services
- Optimized storage technology mixes for microgrids and islanded systems

![](_page_12_Figure_6.jpeg)

# WPTO project: Integrated hydro- energy storage systems (INL, NREL, ANL)

PHIL Implementation of ROR Kaplan turbine generator operating with real BESS

![](_page_13_Figure_2.jpeg)

PHIL emulation of different strategies for ROR HPP black start

![](_page_13_Figure_4.jpeg)

Next step: Testing of developed black start controls on a real ROR plant in Idaho

### Flatirons Campus microgrid operation 7am Sunday, 10/11/2020 – 8am Monday, 10/12/2020

![](_page_14_Figure_1.jpeg)

- BESS - PV - Load - Generator - Wind - Generator(Eaton)

# Thank you

#### www.nrel.gov

Questions? Please, contact vahan.gevorgian@nrel.gov

NREL/PR-5D00-78604

This work was authored by the National Renewable Energy Laboratory, operated by Alliance for Sustainable Energy, LLC, for the U.S. Department of Energy (DOE) under Contract No. DE-AC36-08GO28308. Funding provided by U.S. Department of Energy Office of Energy Efficiency and Renewable Energy Solar and Wind Energy Technologies Offices. The views expressed in the article do not necessarily represent the views of the DOE or the U.S. Government retains and the publisher, by accepting the article for publication, acknowledges that the U.S. Government retains a nonexclusive, paid-up, irrevocable, worldwide license to publish or reproduce the published form of this work, or allow others to do so, for U.S. Government purposes.

![](_page_15_Picture_5.jpeg)