



Overview of ARIES Research Projects Involving Inverter- Based Resources


Vahan Gevorgian, NREL

Power Electronic Grid Interface (PEGI) Platform
Workshop

October 13th, 2020

NREL Flatirons Campus

- Total of 12+ MW variable renewable generation currently
- 7 MVA Controllable Grid Interface (CGI)
- Multi-MW energy storage test facility
- 2.5MW and 5 MW dynamometers (industrial motor drives)
- 13.2 kV medium voltage grid
- 1.5 MW total PV capacity



Gamesa
2 MW

Siemens
2.3 MW

2.5 MW dynamometer

5 MW dynamometer,
7MVA CGI

PV Array
1 MW

1MW / 1MWh BESS

FS PV array

Research Turbines
2 x 600 kW

GE 1.5 MW

NWTC Controllable Grid Platform




Image source: NREL

Main Engineering Challenges for Grids with High Shares of IBRs

- Lowering of system inertia, degrading frequency stability with increasing penetration
- Degrading grid strength, stability in weaker grids
- New protection methods at any level in the grid (low short-circuit current)
- Who and how will be providing grid forming? Why can't we operate all inverters as grid forming? Do we still need grid following? New black-start paradigm? Inrush current issue?
- New stability challenges in inverter dominated grids – control interactions and resonances. New stability evaluation methods (impedance-based stability analysis, etc.).
- How to control new transmission technologies – FACTS, HVDC, multi-terminal HVDC? New roles for synchronous condensers?
- Frequency stability in future inverter–dominated grids and in 100% grids:
 - Future 1: everything is inverter coupled (even hydro), no synchronizing torque, classic frequency stability becomes irrelevant
 - Future 2: We still have some synch generation at 100% (hydro, CSP, etc.), so classic frequency stability still matters.
- Reliability and resiliency of decentralized and autonomous grids, MVDC/LVDC grids
- High fidelity sensing and new data driven state estimation, control and protection methods
- Cyber security in inverter dominated grids

Ongoing Research Projects at FC

7 MVA Controllable Grid Interface #1

Power rating

- 7 MVA continuous
- 39 MVA short circuit capacity (for 2 sec)
- 4-wire, 13.2 kV

Possible test articles


- Types 1, 2, 3 and 4 wind turbines
- PV inverters, energy storage systems
- Conventional generators
- Combinations of technologies

Voltage control (no load THD <1%)

- Balanced and un-balanced voltage fault conditions (ZVRT and 140% HVRT) – independent voltage control for each phase on 13.2 kV terminals
- Response time – 1 millisecond (from full voltage to zero, or from zero back to full voltage)
- Long-term symmetrical voltage variations (+/- 10%) and voltage magnitude modulations (0-10 Hz) – SSR conditions
- Programmable impedance (strong and weak grids)
- Programmable distortions (lower harmonics 3, 5, 7)
- Impedance characterization of inverter-coupled generation
- Full STATCOM functionality

Frequency control

- Fast output frequency control (3 Hz/sec) within 45-65 Hz range
- 50/60 Hz operation
- Can simulate frequency conditions for any type of power system
- PHIL capable (coupled with RTDS, Opal-RT, etc.)
- Test-bed for PMU-based wide-area stability controls



Capabilities

- Balanced and unbalanced over and under voltage fault ride-through tests
- Frequency response tests
- Continuous operation under unbalanced voltage conditions
- Grid condition simulation (strong and weak)
- Reactive power, power factor, voltage control testing
- Protection system testing (over and under voltage and frequency limits)
- Islanding operation
- Sub-synchronous resonance conditions
- 50 Hz tests

20 MVA Controllable Grid Interface

Power rating

- Continuous AC rating - 19.9 MVA at 13.2kV and 34.5 kV
- Overcurrent capability (x5.7 for 3 sec, x7.3 for 0.5 sec)
- 4-wire 13.2 kV or 35.4 kV taps
- Continuous operational AC voltage range: 0 - 40 kVAC
- Continuous DC rating – 10 MW at 5 kVDC

Possible test articles


- Types 1, 2, 3 and 4 wind turbines
- PV inverters, energy storage systems
- Conventional generators
- Combinations of technologies / hybrid systems
- Responsive loads

Voltage control (no load THD <1%)

- Balanced and unbalanced voltage fault conditions (ZVRT, LVRT and 140% HVRT) – independent voltage control for each phase on 13.2 kV and 34.5 kV terminals
- Response time – less than 1 millisecond (from full voltage to zero, or from zero back to full voltage)
- Programmable injection of positive, negative and zero sequence components
- Long-term symmetrical voltage variations (+/- 10%) and voltage magnitude modulations (0-10 Hz) – SSR conditions
- Programmable impedance (strong and weak grids, wide SCR range corresponding to a POI with up to 250 MVA of short circuit apparent power)
- Injection of controlled voltage distortions
- Wide-spectrum (0-2kHz) impedance characterization of inverter-coupled generation and loads
- All-quadrant reactive power capability characterization of any system

Frequency control

- Fast output frequency control (3 Hz/sec) within 45-65 Hz range
- 50/60 Hz operation
- Can simulate frequency conditions for any type of power system
- PHIL capable (can be coupled with RTDS, Opal-RT, Typhoon, etc.)
- Coupled with PMU-based wide-area stability controls validation platform







New features

- 5 kV MVDC grid simulator (PHIL capable)
- Voltage or current source operation
- Seamless transition between voltage and current source modes
- Emulation of full set of resiliency services:
 - Black start
 - Power system restoration schemes
 - Microgrids
- Flexible configurations are possible when combined with CGI#1:
 - Two independent experiments
 - Parallel operation
 - Back-to-back operation
 - Emulation of isolated, partially or fully grid-connected microgrids

SETO Project: PV-BESS Integration

NREL-First Solar Collaboration



Developed and tested various controls for PV-BESS system:


- Dispatchability and flexibility
- Essential reliability services
- Advanced reliability and wide-area stability services
- Black start and islanded operation
- Impedance characterization of PV-BESS system in GFL and GFM modes




SETO Project: Grid Forming PV Inverters

NREL-GE Collaboration


GE Grid Forming PV - Project Pad 5 Concept








Objective: Develop and demonstrate grid forming controls by utility-scale PV inverters



NREL-PG&E Project: GFM BESS Circuits to Enhance Reliance of Distribution Grids





Island forms after CB1 trip




DOE OE Project: SuperFACTS

- Integrated Synchronous Condenser – GFM BESS system
- Scalable solution for transmission, subtransmission and islanded applications
- All types of grid services (market based, reliability and resiliency)
- Robust controls
- Grid strength enhancement
- Black start resource
- Fully scalable solution



WETO Project: Wind as Virtual Synch Generator


Grid Forming GE 2.8 MW DFIG generator



Main Objective: Development, implementation and validation of GFM controls using GE generator/converter platform with NREL's 5 MW dynamometer and Controllable Grid Interfaces


- Provision of reliability services by GFM wind power
- Transient performance by GFM wind power
- Black start and resilience services by GFM wind power

DOE GMCLC: FlexPower Hybrid Plant Demonstration Platform



Optimized Hybrid Energy Systems



- Validation of design optimization tools and operational strategies for hybrid energy storage systems for provision of grid services at various time scales (ms-s-min-hr-day)
- Development and validation of optimized control theory for hybrid energy storage to provide essential reliability and resiliency services to the grid:
 - Optimal ratios between device level, plant level and system level controls
- Design and operation of hybrid renewable-storage plants for improved dispatchability, increased capacity factors and enhanced grid services
- Optimized storage technology mixes for microgrids and islanded systems




* PHIL: Power-Hardware-in-the-Loop

WPTO project: Integrated hydro- energy storage systems (INL, NREL, ANL)

PHIL Implementation of ROR Kaplan turbine generator operating with real BESS



PHIL emulation of different strategies for ROR HPP black start



Next step: Testing of developed black start controls on a real ROR plant in Idaho

Flatirons Campus microgrid operation

7am Sunday, 10/11/2020 – 8am Monday, 10/12/2020



Thank you

www.nrel.gov

Questions? Please, contact vahan.gevorgian@nrel.gov

This work was authored by the National Renewable Energy Laboratory, operated by Alliance for Sustainable Energy, LLC, for the U.S. Department of Energy (DOE) under Contract No. DE-AC36-08GO28308. Funding provided by U.S. Department of Energy Office of Energy Efficiency and Renewable Energy Solar and Wind Energy Technologies Offices. The views expressed in the article do not necessarily represent the views of the DOE or the U.S. Government. The U.S. Government retains and the publisher, by accepting the article for publication, acknowledges that the U.S. Government retains a nonexclusive, paid-up, irrevocable, worldwide license to publish or reproduce the published form of this work, or allow others to do so, for U.S. Government purposes.

